

Milestone Review Flysheet

PDR

Institution Name

University of South Florida

Milestone

PDR

Vehicle Properties	
Diameter (in)	6
Length (in)	133
Loaded Weight (lb)	51
Launch Lug/button Size	1515
Motor Retention	Front end of motor

Stability Analysis	
Center of Pressure (in from nose)	98.5
Center of Gravity (in from nose)	85
Static Stability Margin	2.18
Thrust-to-Weight Ratio	6.22
Rail Size (in) / Length (in)	96

Recovery System Properties				
Drogue Parachute				
Manufacturer/Model		SkyAngle		
Size		Drogue		
Altitude at Deployment (ft)		Apogee		
Velocity at Deployment (ft/s)		114		
Terminal Velocity (ft/s)		63.7		
Recovery Harness Material		Braided Nylon		
Harness Size/Thickness (in)		21.8		
Recovery Harness Length (ft)		24		
Harness/Airframe Interfaces		Forged ¼-inch eye-bolt and quick link connected to a swivel and quicklink		
Kinetic Energy During Descent (ft-lb)	Section 1	Section 2	Section 3	Section 4

Recovery System Properties				
Electronics/Ejection				
Altimeter(s) Make/Model		Missile Works RRC3 Altimeter		
Redundancy Plan		The recovery system electrical circuits shall be completely independent of any payload electrical circuits. The recovery system shall contain redundant altimeters.		
Pad Stay Time (Launch Configuration)		2 Hours		

Motor Properties	
Motor Manufacturer	Cesaroni
Motor Designation	L1090
Max/Average Thrust	1702.1N / 1090 N
Total Impulse	4815 Ns
Mass pre/post Burn (g)	5461 / 2021

Ascent Analysis	
Rail Exit Velocity (ft/s)	35.4
Max Velocity (ft/s)	541
Max Mach Number	0.49
Max Acceleration (ft/s ²)	195
Peak Altitude (ft)	4954

Recovery System Properties				
Main Parachute				
Manufacturer/Model		SkyAngle		
Size		X-large		
Altitude at Deployment (ft)		2000		
Velocity at Deployment (ft/s)		11.33		
Recovery Harness Material		Braided Nylon		
Harness Size/Thickness (in)		60		
Recovery Harness Length (ft)		42		
Harness/Airframe Interfaces		Forged ¼-inch eye-bolt and quick link connected to a swivel and quicklink		
Kinetic Energy Upon Landing (ft-lb)	Section 1 (Nosecone)	Section 2 (Lander)	Section 3 (Altimeter)	Section 4 (Booster)
	5.98	32.89	11.96	28.90

Recovery System Properties	
Electronics/Ejection	
Rocket Locators (Make, Model)	Altus Metrum TELEGPS
Transmitting Frequencies	N/A
Black Power Mass Drogue Parachute (gram)	N/A
Black Power Mass Main Parachute (gram)	N/A

Milestone Review Flysheet

PDR

Institution Name

University of South Florida

Milestone

PDR

Payload/Science	
Succinct Overview of Payload/Science Experiment	The altimeter bay of the launch vehicle will deploy a landing module with three main systems: Vision, Steering, and Landing Gear. The landing module will have stabilize using the propeller blades, as well as guide the rocket. The camera will recognize the proper target pad. The landing gear system will allow for a stable, vertical landing of the lander section.
Identify Major Components	Vision system with camera and visual processing, landing gear system with spring hinges, and steering system with quadcopter propeller blades.
Mass of Payload/Science	N/A

Test Plan Schedule/Status	
Ejection Charge Test(s)	Will be performed at test launch for full scale
Sub-scale Test Flights	Will be performed before CDR
Full-scale Test Flights	Will be performed before FRR

Additional Comments